

Fire Extinguisher 2Kg powder (BSI KITEMARK) BSI KITEMARK SERIES

Fire Extinguisher **2Kg** with One Seam Vessel.

METALLIC BRACKET INCLUDED



CHARACTERISTICS

Approval Type	APRAGAZ, BENOR, BSI, CNBOP, GTC, IGSU, MED, MIRTEC, MPA DRESDEN, NCP - KIWA, NF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Powder
Capacity	2Kg
Extinguishing Agent	ZX PD Standard N
Operating Temperature	-30 ~ +60 °C
Max Allowable Pressure	17 bar
Test Pressure	30 bar
Volume of Equipment	2,4 L
Cylinder Height	305±2 mm
Cylinder Diameter	110±1 mm
Cylinder Neck Thread	M24x1,5
Cylinder Material	DC01 / DC03
Valve Material	CuZn40Pb2
Safety Valve	22-27 bar
Approx. gross Weight	3,84 kg
Approx. Dimensions	125x125x390 mm
Paint Finish	RAL 3000
Packaging Details	1 pcs.



Issue Date: 21/11/2024

Information may change

IMPORTER: SAVS, DOCTERSKAMPSTRAAT 5, 5222 AM 'S-HERTOGENBOSCH, THE NETHERLANDS, TEL.: +31(0)85-4014173, MAIL: INFO@SAVS.ME
www.savs.me