

Fire Extinguisher 6 Lt with Ecological Fluorine Free Foam Fluorine Free

Fire Extinguisher 6Lt water with additive, with one seam vessel, Internal Plastic Layer and Safety Release Valve. 100% PFAS FREE
METALLIC BRACKET INCLUDED



CHARACTERISTICS

| | |
|------------------------|----------------------------------|
| Approval Type | BENOR, GTC, MED, NCP - KIWA, VKF |
| Extinguisher Type | Portable |
| Pressure Type | Stored Pressure |
| Suppression Agent Type | Fluor Free, Water |
| Capacity | 6Lt |
| Extinguishing Agent | Water with additive |
| Operating Temperature | +5 to +60 °C °C |
| Max Allowable Pressure | 18 bar |
| Test Pressure | 27 bar |
| Volume of Equipment | 7,9 L |
| Cylinder Height | 470±5 mm |
| Cylinder Diameter | 160±1,5 mm |
| Cylinder Neck Thread | M30x1,5 |
| Cylinder Material | DC01 (St12) |
| Valve Material | HPb59-1 (Nikel Plated) |
| Safety Valve | 19-26 bar |
| Approx. gross Weight | 10,5 kg |
| Approx. Dimensions | 630x200 mm |
| Paint Finish | RAL 3000 |



Issue Date: 09/01/2025

Information may change