

6Lt ABF Fire Extinguisher Portable

Fire Extinguisher 6Lt with one seam vessel with INTERNAL PLASTIC LAYER and Pressure Gauge Safety Release Valve.

METALLIC BRACKET INCLUDED



CHARACTERISTICS

Approval Type	APRAGAZ, BENOR, IGSU, MED, MIRTEC, NCP - KIWA, NF, TSE
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Wet Chemical
Capacity	6Lt
Extinguishing Agent	Eco Dare ABF -30°C/M
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,7 L
Cylinder Height	470±5 mm
Cylinder Diameter	160±1,5 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	10,6 kg
Approx. Dimensions	640x210 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



Issue Date: 21/11/2024

Information may change

IMPORTER: SAVS, DOCTERSKAMPSTRAAT 5, 5222 AM 'S-HERTOGENBOSCH, THE NETHERLANDS, TEL.: +31(0)85-4014173, MAIL: INFO@SAVS.ME

www.savs.me