

SAVS


saves lives

CODE: SAVS-6SAF-LI-FF

ERP: 0501149

Portable Fire Extinguisher 6Lt for Lithium Batteries Portable

Fire Extinguisher 6Lt Hydrogel, with One Seam Vessel with INTERNAL PLASTIC LAYER and External Thread, Pressure Gauge Safety Release Valve and Gauge Non Return Valve. Appropriate for use at Lithium Ion Battery Fires. Metallic Bracket Included



CHARACTERISTICS

Approval Type	BENOR, BSI, CE, MED, MIRTEC, NCP - KIWA, NF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Agent for Li-on Batteries
Capacity	6Lt
Fire Rating	13A 25F
Extinguishing Agent	HydroGel BM 048
Operating Temperature	+5 ~ +60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	7,8 L
Cylinder Height	477±3 mm
Cylinder Diameter	162±2 mm
Cylinder Neck Thread	M74x1.5
Valve Material	AA6061 (anodized)
Cylinder Material	DC04/DC03
Safety Valve	22~27 bar
Approx. gross Weight	~10,2 kg
Approx. Dimensions	580x180 mm
Paint Finish	RAL3000
Discharge time	47.8 sec



Issue Date: 20/02/2025

Information may change

IMPORTER: SAVS, DOCTERSKAMPSTRAAT 5, 5222 AM 'S-HERTOGENBOSCH, THE NETHERLANDS, TEL.: +31(0)85-4014173, MAIL: INFO@SAVS.ME
www.savs.me